

OUTDOOR DECORATIVE LUMINAIRES

BEAUTIFUL LIGHT IS NOT A QUESTION OF SPACE: OUR FACADE AND PATHWAY LUMINAIRES

OUTDOOR

Page 182

OUTDOOR LANTERN

OUTDOOR EDGE

OUTDOOR UPDOWN

OUTDOOR BELT

OUTDOOR SPOT

OUTDOOR ROUND

OUTDOOR SQUARE

OUTDOOR INDIRECT

VALUE
CLASS



OPTIMUM OUTDOOR LIGHTING

- Attractive design combined with high-quality materials and finishes
- Robust and weatherproof (up to IP54)
- Appealing warm white (3,000 K) illumination for a welcoming atmosphere
- Easy installation, all necessary accessories included

Our facade and directional luminaires stand out for the materials used and their design, and provide pleasant outdoor lighting.



OUTDOOR

Decorative outdoor luminaires



PRODUCT FEATURES

- Die-cast aluminum housing
- Type of protection: IP54
- Available as wall, ceiling and bollard luminaires
- Bright and functional outdoor LED luminaires
- Outdoor Facade Edge also available as a sensor version

PRODUCT BENEFITS

- Energy-efficient thanks to LED technology
- Easy and quick installation
- Homogeneous light output
- 5 years guarantee

AREAS OF APPLICATION

- Outdoor
- Building facades
- Entrance lighting
- Gardens, balconies and other outdoor areas

EQUIPMENT / ACCESSORIES

- Complete mounting and connecting accessories included

¹ Refer to www.ledvance.com/guarantee for precise conditions | ² Versions with integrated sensor available

The pictures shown in the catalog are for illustration purposes only. For information on size and color, please refer to the product table.

Product name	Segmentation	GTIN (EAN)	RE-PLACEMENT FOR	W	lm	lm/W	K	L70 ¹	°
O FACADE SPOT 8 W 3000 K IP54 GY	■	4058075074712	1x40W GLS	8	440	55	3000	30000	110
O FACADE SPOT 8 W 3000 K IP54 WT	■	4058075074736	1x40W GLS	8	460	60	3000	30000	110
O FACADE EDGE 12 W 3000 K IP54 GY	■	4058075074750	1x60W GLS	12	740	60	3000	30000	110
O FACADE EDGE 12 W 3000 K IP54 WT	■	4058075074774	1x60W GLS	12	770	65	3000	30000	107
O FACADE EDGE SENSOR 12 W 3000 K IP54 S GY	■	4058075074798	1x60W GLS	12	740	60	3000	30000	107
O FACADE EDGE SENSOR 12 W 3000 K IP54 S WT	■	4058075074811	1x60W GLS	12	770	65	3000	30000	107
O FACADE LANTERN 12 W 3000 K IP54 GY	■	4058075074835	1x40W GLS	12	610	50	3000	30000	210
O BOLLARD 500 LANTERN 12 W 3000 K IP54 GY	■	4058075074859	1x40W GLS	12	610	50	3000	30000	210
O BOLLARD 900 LANTERN 12 W 3000 K IP54 GY	■	4058075074873	1x40W GLS	12	610	50	3000	30000	210
O SURFACE RD 13 W 3000 K IP54 GY	■	4058075074897	1x40W GLS	13	480	35	3000	30000	100
O SURFACE RD 13 W 3000 K IP54 WT	■	4058075074910	1x40W GLS	13	600	45	3000	30000	100
O SURFACE SQ 13 W 3000 K IP54 GY	■	4058075074934	1x40W GLS	13	480	35	3000	30000	100
O SURFACE SQ 13 W 3000 K IP54 WT	■	4058075074958	1x40W GLS	13	600	45	3000	30000	100
O FACADE BELT RD 11 W 3000 K IP54 GY	■	4058075074972	1x40W GLS	11	400	35	3000	30000	335
O FACADE BELT SQ 11 W 3000 K IP54 GY	■	4058075074996	1x40W GLS	11	410	35	3000	30000	340
O FACADE IND RD 13 W 3000 K IP54 GY	■	4058075075016	1x40W GLS	13	480	35	3000	30000	240
LED FACADE INDIRECT 13 W 3000 K RD WT	■	4058075075030	1x60W GLS	13	640	50	3000	30000	240
O FACADE UPDOWN 12 W 3000 K IP54 GY	■	4058075075054	1x60W GLS	12	700	60	3000	30000	280
O FACADE UPDOWN 12 W 3000 K IP54 WT	■	4058075075078	1x60W GLS	12	710	60	3000	30000	280



Product name	CRI	IK	g	L x W x H [mm]	Ø x H [mm]	No.
O FACADE SPOT 8 W 3000 K IP54 GY	≥80	IK06	600	135 x 90 x 140		11
O FACADE SPOT 8 W 3000 K IP54 WT	≥80	IK06	600	135 x 90 x 140		-
O FACADE EDGE 12 W 3000 K IP54 GY	≥80	IK06	1300	168 x 100 x 273		9
O FACADE EDGE 12 W 3000 K IP54 WT	≥80	IK06	1300	168 x 100 x 273		-
O FACADE EDGE SENSOR 12 W 3000 K IP54 S GY	≥80	IK06	1300	168 x 100 x 273		10
O FACADE EDGE SENSOR 12 W 3000 K IP54 S WT	≥80	IK06	1300	168 x 100 x 273		-
O FACADE LANTERN 12 W 3000 K IP54 GY	≥80	IK06	1300	176 x 110 x 240		8
O BOLLARD 500 LANTERN 12 W 3000 K IP54 GY	≥80	IK06	1900	110 x 500		6
O BOLLARD 900 LANTERN 12 W 3000 K IP54 GY	≥80	IK06	3100	110 x 900		7
O SURFACE RD 13 W 3000 K IP54 GY	≥80	IK06	770	202 x 45		-
O SURFACE RD 13 W 3000 K IP54 WT	≥80	IK06	770	202 x 45		5
O SURFACE SQ 13 W 3000 K IP54 GY	≥80	IK06	910	202 x 202 x 45		-
O SURFACE SQ 13 W 3000 K IP54 WT	≥80	IK06	910	202 x 202 x 45		4
O FACADE BELT RD 11 W 3000 K IP54 GY	≥80	IK06	720	60 x 240 x 142		-
O FACADE BELT SQ 11 W 3000 K IP54 GY	≥80	IK06	750	60 x 240 x 142		3
O FACADE IND RD 13 W 3000 K IP54 GY	≥80	IK06	790	150 x 118		-
LED FACADE INDIRECT 13 W 3000 K RD WT	≥80	IK06	790	150 x 118		2
O FACADE UPDOWN 12 W 3000 K IP54 GY	≥80	IK06	480	55 x 90 x 160		1
O FACADE UPDOWN 12 W 3000 K IP54 WT	≥80	IK06	480	55 x 90 x 160		-

SENSOR PROPERTIES

Product name	Type of sensor	Sensor technology	Detection threshold of daylight sensor	Detection range of motion sensor	Sensor detection angle	Sensor controlled switching time
OUTDOOR FACADE EDGE	Motion/Light	Passive infrared (PIR)	10/2000 lx	3/6 m	120 °	5 s/30 s/1 min/3 min/5 min min/8

¹ t [h]: L70/B50 @ 25 °C (Ta) / t [h]: L80/B10 @ 25 °C (Ta)