



## Pro Series

### Lumen Output / Meter (lm/m)



DU-F-H2835-80-24-9.60-10mm	1152	1248	1315	1354	1421	1421	1421	1392	1277
DU-F-H2835-160-24-14.4-10mm	1728	1901	2002	2045	2146	2146	2174	2102	1958
DU-F-H2835-240-24-21.6-14mm	2419	2657	2851	2894	3046	3110	3089	3024	2830
DU-F-H2835-288-24-25.92-22mm	2903	3188	3421	3473	3655	3732	3707	3629	3396
DU-F-H2835-416-24-37.44-50mm	4193	4605	4942	5017	5279	5391	5354	5242	4905
DU-F-H2835-432-24-38.88-28mm	4666	4977	5210	5560	5871	5832	5871	5676	5288

### Technical Specifications

Model	CRI	Voltage input	Power /meter	IP rating	Size	LED's /meter	Cutting unit
DU-F-H2835-80-24-9.60-10mm	>80	24 VDC	9.6 W/m	IP20	5000 x 10mm	80 pcs/m	100mm
DU-F-H2835-160-24-14.4-10mm			14.4 W/m		5000 x 10mm	160 pcs/m	50mm
DU-F-H2835-240-24-21.6-14mm			21.6 W/m		5000 x 14mm	240 pcs/m	33.3mm
DU-F-H2835-288-24-25.92-22mm			25.92 W/m		5000 x 22mm	288 pcs/m	83.33mm
DU-F-H2835-416-24-37.44-50mm			37.44 W/m		5000 x 50mm	416 pcs/m	38.46mm
DU-F-H2835-432-24-38.88-28mm			38.88 W/m		5000 x 28mm	432 pcs/m	18.5mm