




**Cable structure**



Electrolytic copper wire, Ø 0.64 mm (AWG22)

Physical foam PE, Ø 2.90 mm  
70°C, EN 50290-2-23

Cu-Pet foil min. 100% coverage  
Electrolytic braided copper wire

PVC - RAL 6018 Green, Ø 4.30 mm  
TM51 70°C, EN 50290-2-22

**Application**

Utilising physical foam insulation technology, cables have a rated impedance of 75 ohms and comply with EN 50117. They are primarily used in Cable TV, individual/central satellite distribution and CCTV security camera systems. Thanks to the small-diameter design, the cables are suitable for flush-mount electrical installation in walls and ceilings of the renovated buildings.

**Specifications**

Operating temperature		-30°C ...+70°C	
Bending radius	min.	10 x D	
Impedance		75 ± 3 Ω	
Capacitance		54 ± 2 pF/m	
Velocity of propagation		(83 ± 2)%	
Insulation resistance	min.	2 GΩ x km	
Operating voltage	max.	1000 V	
Test voltage		2500 V	
Attenuation @20°C	max.	50 MHz	7.26 dB/100 m
		200 MHz	14.23 dB/100 m
		470 MHz	21.91 dB/100 m
		860 MHz	29.96 dB/100 m
		1000 MHz	32.43 dB/100 m
		2150 MHz	48.82 dB/100 m
		2400 MHz	51.83 dB/100 m
		3000 MHz	58.59 dB/100 m
Return loss <sup>1)</sup>		5-470 MHz	> 20 dB
		470-1000 MHz	> 18 dB
		1000-2000 MHz	> 16 dB
		2000-3000 MHz	> 15 dB
Segregation class		"c" EN 50174-2	

**Standards** EN 50117, IEC 61196

**Fire performance**

Vertical flame propagation EN 60332-1-2

**EU declaration of conformity**

LVD	Low Voltage Directive	2014/35/EU
RoHS	Restriction of Hazardous Substances	2011/65/EU

**Cable assembly length**

Satellite distribution <sup>2)</sup>	2150 MHz	40 m
VHF/UHF distribution <sup>3)</sup>	860 MHz	100 m
S-band Cable TV distribution <sup>3)</sup>	470 MHz	140 m

<sup>1)</sup> According to EN 50117, 3 return loss peaks, whose value exceeds the limit by a maximum of 4 dB, are permissible.

<sup>2)</sup> Maximum applicable length in 20 dBμV satellite distribution without line amplifier

<sup>3)</sup> Maximum applicable length in 30 dBμV VHF/UHF and S-band Cable TV without line amplifier

Product code	Cable structure	Diameter [mm]	Copper weight [kg/km]	Cable weight [kg/km]	Sheath colour	Packaging [m]
307052	Mini U/6 PHY-PVC Cu/Cu	4.30	11	23	Green (RAL 6018)	100/250/500/1000
307109	Mini U/6 PHY-PVC Cu/Cu	4.30	11	23	White (RAL 9003)	100/250/500/1000

Specifications may vary depending on technical modifications.