



Standard Series



Product Features

- High brightness and luminous efficiency
- Good attenuation function, long service life of the chip
- FPC flexible board is used, which can be bent appropriately
- Excellent weather and UV resistance
- 0-1/10V dimming, DALI dimming, smart (optional)

Lumen Output / Meter (lm/m)

2800
to 3200
K

4000
to 4500
K

5000
to 5500
K

6500
to 7000
K

9000
to 12000
K

	2800 to 3200 K	4000 to 4500 K	5000 to 5500 K	6500 to 7000 K	9000 to 12000 K
DU-F-2835D-60-24-4.8-8mm	417	427	441	451	360
DU-F-2835D-120-24-9.6-8mm	864	883	912	931	749
DU-F-2835D-120-24-14.4-8mm	1296	1325	1368	1397	1123
DU-FW-2835D-60-24-4.8-8mm	417	427	441	451	360
DU-FW-2835D-120-24-9.6-8mm	864	883	912	931	749
DU-FW-2835D-120-24-14.4-8mm	1296	1325	1368	1397	1123
DU-FWT-2835D-60-24-4.8-10mm	417	427	441	451	360
DU-FWT-2835D-120-24-9.6-10mm	864	883	912	931	749
DU-FWT-2835D-120-24-14.4-10mm	1296	1325	1368	1397	1123

Technical Specifications

Model	CRI	Voltage input	Power /meter	IP rating	Size	LEDs /meter	Cutting unit	
DU-F-2835D-60-24-4.8-8mm	>80	24 VDC	4.8 W/m	IP20	5000 x 8mm	60 pcs/m	100mm	
DU-F-2835D-120-24-9.6-8mm			9.6 W/m		5000 x 8mm	120 pcs/m	50mm	
DU-F-2835D-120-24-14.4-8mm			14.4 W/m		5000 x 8mm	120 pcs/m	50mm	
DU-FW-2835D-60-24-4.8-8mm			IP65	4.8 W/m	5000 x 8mm	60 pcs/m	100mm	
DU-FW-2835D-120-24-9.6-8mm				9.6 W/m	5000 x 8mm	120 pcs/m	50mm	
DU-FW-2835D-120-24-14.4-8mm				14.4 W/m	5000 x 8mm	120 pcs/m	50mm	
DU-FWT-2835D-60-24-4.8-10mm				IP67	4.8 W/m	5000 x 10mm	60 pcs/m	100mm
DU-FWT-2835D-120-24-9.6-10mm					9.6 W/m	5000 x 10mm	120 pcs/m	50mm
DU-FWT-2835D-120-24-14.4-10mm					14.4 W/m	5000 x 10mm	120 pcs/m	50mm

