



LED STRIP

LED STRIP : An LED strip light is a flexible circuit board that is populated with LEDs that you can stick almost anywhere you want to add powerful lighting in a variety of colors and brightnesses.





Input Voltage Direct Voltage (DC 12V)



Input Voltage Direct Voltage (DC 24V)



Input Voltage Alternating Voltage (DC 24V)



surface-mounted device LEDs (SMD LEDs)



(chip on board)



IP RATE : A way of showing the effectiveness of electrical enclosures in blocking foreign bodies such as dust, moisture, liquids, and accidental contact



The Base of LED strip width, typically measured in millimeters, refers to the physical dimension of the strip from one edge to the other, with common widths ranging from 5mm to 20mm.



The type of LED Chip



Color Rendering Index (CRI) is a measurement of how natural colors render under an artificial white light source when compared with sunlight.



allowing for customizable lighting levels or adjusting its brightness to suit different preferences.



Our strips can be cut every few Centimeter, meaning you can easily customize the strip to fit your space.



Our strips can be cut every few Centimeter, meaning you can easily customize the strip to fit your space.



Peel & Stick The back of the strip is fitted with a strong 3M brand adhesive tape, allowing you to peel and stick lights to many different surfaces.



What Can LED Strips Do?

Our LED strip lights and accessories provide beautiful lighting solutions for a wide range of projects and applications.

Residential Applications -



Commercial Applications



Restaurant and Bars



Signage Lighting



Display / Merchandise



Specialty Applications



Events and Stages



Terrarium Lighting



Ultraviolet (UV)



Art Displays

COB LED STRIP





	LVS-COB-288L
Power:	8 W
Lumen:	80-90 lm
Array:	Single Line
Color temp:	3000-6500
PCB:	8mm
FBC:	11.5x6.5 mm
Input Voltage:	AC220V
IP Rate:	IP65
Led QTY:	288 Led/m
CRI:	>80
Length\Roll:	50 - 100 m









Application



stairs

Facade lighting





Emergency lighting, road marking

commercial light and shop windows





	LVS-COB320D	LVS-COB480D
Power:	9.6W	12W
Color temp:	3000-6500	3000-6500
PCB:	8 mm	8 mm
Input Voltage:	DC 24V	DC 24V
IP Rate:	IP20	IP20
CRI:	>80	>80
Led QTY:	320 Led/m	480 Led/m
Length\Roll:	6 m	6 m











Application



stairs

Facade lighting

theaters

Emergency lighting, road marking

commercial light and shop windows

Bridges

